



Technical Data Sheet

Waterborne wax

Water based wax with Marseille soap for interior use with non-yellowing and water repelling properties, ideal to protect and to gloss decorative finishes, polished plasters and stuccos.



INTENDED USE

As a protective, waxing top coat for decorative finishes.



SURFACE TREATMENT

Surfaces to treat must be perfectly dry and clean.



APPLICATION

Apply a coat of Easywax with a clean sponge or a non-fluffy cloth, evenly over the entire surface. As soon as the product starts to wither, before it dries, buff and polish the surface well.



THINNING

Ready to use.



AVERAGE SPREAD RATE

15-20 sq.m./litre



DRYING TIME AT 25° C

About 12 - 18 hours



SPECIFIC GRAVITY

1000 ± 20 g/l



ADVICES

Do not apply with air and surface temperatures below 5°C and above 28°C. All the products must be protected from freezing and well stored under cover. Carefully verify spread rates and the surface area to be coated to avoid running short of product during the working process and reducing the risk of differences in tones. The spread rates of the products have only an indicative value and may vary notably according to the substrate condition and the skill of the applicator.



PAKAGING

containers lt. 0.8x6 units;



V.O.C. (Directive 2004/42/CE)

11 g/l; Cat. L CA (Max. Value 200 g/l)

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

